



PCN / EOL Notification

Product Change Notification Number: CC101301

Notification Date*: April 29, 2010

Title: INTRODUCTION OF A NEW 1.7V 2K SERIAL EEPROM

Product Identification:

All Wafers and Packages of the AT24C02B, Industrial Temperature Grade (-40C to +85C)

Replacement Part Numbers are shown in Attachment A

Reason for Change:

☐ Design	☒ Processing	☐ Logistics
☐ Manufacturing Location	☐ Quality/Reliability	☐ Material

Change Description:

Atmel is introducing a new Serial EEPROM with an operating range of 1.7V to 5.5V: AT24C02C.

The NEW AT24C02C will now replace all AT24C02B devices.

The new packaged devices offered with the AT24C02C are as follows:

8-lead JEDEC SOIC:	ROHS compliant/Lead-Free/Halogen-Free/NiPdAu plating.
8-lead TSSOP:	ROHS compliant/Lead-Free/Halogen-Free/NiPdAu plating.
8-lead UDFN (Mini-MAP):	ROHS compliant/Lead-Free/Halogen-Free/NiPdAu plating.
8-lead PDIP:	ROHS compliant/Lead-Free/Halogen-Free/Matte Tin plating.
5-lead SOT23:	ROHS compliant/Lead-Free/Halogen-Free/Matte Tin plating.
8-ball VFBGA (dBG2):	ROHS compliant/Lead-Free/Halogen-Free/Matte Tin plating.

Atmel will also support die sales shipment in Wafer Form, Tape and Reel and Bumped Wafers

Identification Method to Distinguish Change:

NEW part numbers have been created by adding a "C" to the suffix of the catalogue part number:

The AT24C02B shall be identified as the AT24C02C.

Qualification Data:

☒ available	☐ will be available in WW___	☐ not applicable
☒ available	☐ will be available in WW	☐ not applicable

Samples:

Quantifiable Impact on Quality & Reliability:

The new devices are a form, fit and function equivalent of the current devices, which meet all databook specifications.

Forecasted Availability Date:

Now

Last Time Buy Date:

October 27, 2010

Last Ship Date:

April 27, 2011

* All orders placed after the notification date are **non-cancellable** and **non-returnable (NCNR)**.

Atmel Contact: pcnadm@atmel.com

Atmel will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice. All correspondence must be sent to the Atmel Contact e-mail address listed above.

Information provided herein is in connection with Atmel products and this information is provided "AS IS". Atmel assumes no responsibility for any errors that may appear in this document. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

Attention Distributors: Product(s) identified in this notification will become obsolete and as such this EOL notification will act as the official written notification. All obsolete products will be listed in the next published quarterly distributor price book, following an PCN/EOL change, and listed on the obsolescence form which accompanies said price book. Within thirty (30) days from the published date of the price book, Distributor shall notify Atmel in writing of Distributor's then current inventory of the obsolete product.

ATMEL Colorado Springs • 1150 E, Cheyenne Mtn, Blvd Colorado Springs • CO 80906 USA

Attachment A

This is the listing for standard datasheet offering, PCN also applies to all (customer specific) special CAN part numbers that are not listed in the table below:

EOL Part Number	Replacement Part Number	Carrier Type
AT24C02B-PU	AT24C02C-PUM	Bulk
AT24C02B-TH-B	AT24C02C-XHM-B	Bulk
AT24C02B-TH-T	AT24C02C-XHM-T	T/R
AT24C02B-TSU-T	AT24C02C-STUM-T	T/R
AT24C02BN-SH-B	AT24C02C-SSHM-B	Bulk
AT24C02BN-SH-T	AT24C02C-SSHM-T	T/R
AT24C02BY6-YH-T	AT24C02C-MAHM-T	T/R
AT24C02BU3-UU-T	AT24C02C-CUM-T	T/R
AT24C02B-W-11	AT24C02C-WWU11M	Wafer Form

Attachment B

Top Side Marking

AT24C02C-PUM

```

                Seal Year
TOP MARK      | Seal Week
              | | |
|---|---|---|---|---|---|---|
 A   T   M   L   U   Y   W   W
|---|---|---|---|---|---|---|
 0   2   C   M               @
|---|---|---|---|---|---|---|
 *           Lot Number
|---|---|---|---|---|---|---|
 |
Pin 1 Indicator (Dot)

```

Y = SEAL YEAR	WW = SEAL WEEK
8: 2008 2: 2012	02 = Week 2
9: 2009 3: 2013	04 = Week 4
0: 2010 4: 2014	:: : :::: :
1: 2011 5: 2015	:: : :::: ::
	50 = Week 50
	52 = Week 52

@ = Country of Assembly
No Bottom Mark

AT24C02C-SSHM-T/B

```

                Seal Year
TOP MARK      | Seal Week
              | | |
|---|---|---|---|---|---|---|
 A   T   M   L   H   Y   W   W
|---|---|---|---|---|---|---|
 0   2   C   M               @
|---|---|---|---|---|---|---|
 *           Lot Number
|---|---|---|---|---|---|---|
 |
Pin 1 Indicator (Dot)

```

Y = SEAL YEAR	WW = SEAL WEEK
8: 2008 2: 2012	02 = Week 2
9: 2009 3: 2013	04 = Week 4
0: 2010 4: 2014	:: : :::: :
1: 2011 5: 2015	:: : :::: ::
	50 = Week 50
	52 = Week 52

@ = Country of Assembly
No Bottom Mark

AT24C02C-CUM-T

TOP MARK

```

|---|---|---|---|
 0   2   C   U
|---|---|---|---|
 Y   M   T   C
|---|---|---|---|
|<-- Pin 1 This Corner

```

Y = ONE DIGIT YEAR CODE

8: 2008 1: 2011
 9: 2009 2: 2012
 1: 2011 3: 2013

M = SEAL MONTH (USE ALPHA DESIGNATOR A-L)

A = JANUARY
 B = FEBRUARY
 " " " " " " " " " " " "

J = OCTOBER
 K = NOVEMBER
 L = DECEMBER

TC = TRACE CODE (ATMEL LOT
 NUMBERS TO CORRESPOND
 WITH TRACE CODE LOG BOOK)
 (e.g. XX = AA, AB...YZ, ZZ)

AT24C02C-MAHM-T

TOP MARK

```

|---|---|---|
 0   2   C
|---|---|---|
 H   M   @
|---|---|---|
 Y   T   C
|---|---|---|
  *
  |
Pin 1 Indicator (Dot)

```

Y = YEAR OF ASSEMBLY

TC = TRACE CODE (ATMEL LOT
 NUMBERS TO CORRESPOND
 WITH TRACE CODE LOG BOOK)
 (e.g. XX = AA, AB...YZ, ZZ)

Y = SEAL YEAR

8: 2008 0: 2012 @ = Country of
 9: 2007 1: 2013 Assembly
 0: 2010 2: 2014
 1: 2011 3: 2015

AT24C02C-XHM-T/B

TOP MARK

```

Pin 1 Indicator (Dot)
|
* |---|---|---|---|---|---|
  A   T   H   Y   W   W
  |---|---|---|---|---|---|
  0   2   C   M   @
|---|---|---|---|---|---|
ATMEL LOT NUMBER
|---|---|---|---|---|---|

```

Y = SEAL YEAR WW = SEAL WEEK
 8: 2008 2: 2012 02 = Week 2
 9: 2009 3: 2013 04 = Week 4
 0: 2010 4: 2014 :: : : : : :
 1: 2011 5: 2015 52 = Week 52

@ = Country of Assembly
 No Bottom Mark

AT24C02C-STUM-T

TOP MARK

```

Line 1 -----> |---|---|---|---|---|
                  2   C   M   W   U
                  |---|---|---|---|---|
                  *
                  |
Pin 1 Indicator (Dot)

```

2C = Device
 M = Voltage Indicator
 W = Write Protect Feature
 U = Material Set
 Pin 1 Indicator (Dot)

BOTTOM MARK

```

|---|---|---|---|
 Y   M   T   C
|---|---|---|---|

```

Y = One Digit Year Code
 M = Seal Month
 TC = Trace Code