



PCN / EOL Notification

Product Change Notification Number: **CC121604**

Notification Date*: July 12, 2012

Title: 64-Kbit SPI Interface Automotive Grade (-40C to 125C) Serial EEPROM (AT25640A) Process Geometric Shrink and Device Enhancement

Product Identification:

All Packages of the Automotive Temperature Grade (-40C to +125C) AT25640A

Reason for Change:

☒ Material / Composition	☒ Design / Firmware	☐ Manufacturing Location
☒ Processing / Manufacturing	☐ Logistics	☐ Quality / Reliability

Change Description:

Atmel has performed a process geometry shrink of the Serial EEPROM Automotive Temperature Grade AT25640A device (SPI interface, 64-Kbit density) from .35 μ to .25 μ . The catalog part number AT25640A will be replaced by AT25640B (see Table 1). The new devices are pin-to-pin and functionally backward compatible with the current AT25640A devices with the following exceptions and enhancements.

Extended-VCC Operation

With a growing number of application segments moving to lower supply voltages, Atmel is developing next generation devices to meet the needs of these lower voltages. These voltage ranges are used by various MCUs, SoCs, and ASICs as process lithographies for such products continue to reduce. To address these voltage requirements, Atmel has designed the AT25640B devices to operate over a 2.5V to 5.5V range versus the previous 2.7V to 5.5V range.

Conversion to Nickel-Palladium-Gold (NiPdAu) lead finish

New devices will be available in the more robust NiPdAu lead finish. The NiPdAu lead finish complies with "green" packaging standards, and all package options remain RoHS compliant and Pb/Halide/Halogen-free. The "P" designation as part of the package designator suffix in the catalog part number identifies the NiPdAu lead finish for Automotive Temperature grade product.

Package material set changes

Atmel assembly subcontractor, Amkor Technology Philippines, SOIC and TSSOP package material sets will change as noted in the following table:

ATP	SOIC		TSSOP	
Material Set	From	To	From	To
Die Attach	Ablebond 84-1 LMISR4	Ablebond 8290	Ablebond 8290	NO Change
Wire Diameter	0.8 mil Au	0.6 mil Au	0.8 mil Au	0.6 mil Au
Mold Compound	Sumitomo EME-G700	Nitto-GE900S	Sumitomo EME-G700	Hitachi CEL-8240HF 10P
Lead Finish	Matte Sn	NiPdAu	Matte Sn	NiPdAu

Delivery Options

To further stream line the shipping and handling process, Atmel is eliminating bulk delivery options. The new AT25640B devices will be offered in Tape and Reel only.

Identification Method to Distinguish Change:

NEW catalog part numbers use "B" suffix for the device revision (AT25640A changes to AT25640B). Please refer to Attachment A for part marking scheme.

Table 1.

This is the listing for standard datasheet offering, PCN also applies to all (customer specific) special CAN part numbers that are not listed in the table below:

EOL Part Number	Replacement Part Number	Package	Carrier Type
AT25640AN-10SQ-2.7 ¹	AT25640B-SSPD-T ³	SOIC	T/R, 4K per reel
AT25640AN-10SQ-2.7 SL383 ²	AT25640B-SSPD-T ³	SOIC	T/R, 4K per reel
AT25640A-10TQ-2.7 ¹	AT25640B-XPD-T ³	TSSOP	T/R, 5K per reel
AT25640A-10TQ-2.7 SL383 ²	AT25640B-XPD-T ³	TSSOP	T/R, 5K per reel

Notes:

1. Bulk will no longer be an ordering option, Tape and Reel ordering only offered
2. SL383 will be eliminated and replaced with "-T" to denote Tape and Reel
3. Please reference qualification pack for further details

Qualification Data:	☒ Available	☐ Will be available (mm/dd/yr):	☐ Not Applicable
Samples:	☒ Available	☐ Will be available (mm/dd/yr):	☐ Not Applicable

Quantifiable Impact on Quality & Reliability:

None

Forecasted Availability Date: Now

Last Time Buy Date: December 31, 2012

Last Ship Date: June 25, 2013

**All orders placed after the notification date are non-cancellable and non-returnable (NCNR).*

Atmel Contact: pcnadm@atmel.com

Information provided herein is in connection with Atmel products and this information is provided "AS IS". Atmel assumes no responsibility for any errors that may appear in this document. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

Attention Distributors: Product(s) identified in this notification will become obsolete and as such this EOL notification will act as the official written notification. All obsolete products will be listed in the next published quarterly distributor price book, following an PCN/EOL change, and listed on the obsolescence form which accompanies said price book. Within thirty (30) days from the published date of the price book, Distributor shall notify Atmel in writing of Distributor's then current inventory of the obsolete product

CUSTOMER ACKNOWLEDGEMENT OF RECEIPT: Atmel requests you acknowledge receipt of this PCN / EOL. Please complete and email to the Atmel Contact listed above. In your acknowledgement, you can grant approval or request additional information. **Atmel will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice.**

Company: Name: Title: Date: Email Address: Location: Comments:	
--	--

Attachment A

8 lead SOIC			8 lead TSSOP																						
3 Rows of 8 Characters			3 Rows 2 of 6 and 1 of 7 Characters																						
Catalog Number: AT25080B Catalog Number: AT25160B Catalog Number: AT25320B Catalog Number: AT25640B			Catalog Truncation: ### = 58B Catalog Truncation: ### = 5AB Catalog Truncation: ### = 5BB Catalog Truncation: ### = 5CB																						
<table border="1"><thead><tr><th colspan="3">Date Codes</th></tr><tr><th>Y - Year</th><th>M - Month</th><th>WW - Work Week of Assembly</th></tr></thead><tbody><tr><td>2: 2012 6: 2016</td><td>A: January</td><td>02: Week 2</td></tr><tr><td>3: 2013 7: 2017</td><td>B: February</td><td>04: Week 4</td></tr><tr><td>4: 2014 8: 2018</td><td>.</td><td>.</td></tr><tr><td>5: 2015 9: 2019</td><td>L: December</td><td>52: Week 52</td></tr></tbody></table>			Date Codes			Y - Year	M - Month	WW - Work Week of Assembly	2: 2012 6: 2016	A: January	02: Week 2	3: 2013 7: 2017	B: February	04: Week 4	4: 2014 8: 2018	.	.	5: 2015 9: 2019	L: December	52: Week 52	<table border="1"><thead><tr><th>Voltages</th></tr></thead><tbody><tr><td>D: 2.5v min</td></tr></tbody></table>			Voltages	D: 2.5v min
Date Codes																									
Y - Year	M - Month	WW - Work Week of Assembly																							
2: 2012 6: 2016	A: January	02: Week 2																							
3: 2013 7: 2017	B: February	04: Week 4																							
4: 2014 8: 2018	.	.																							
5: 2015 9: 2019	L: December	52: Week 52																							
Voltages																									
D: 2.5v min																									
<table border="1"><thead><tr><th>Trace Code</th></tr></thead><tbody><tr><td>XX - Trace Code (ATMEL Lot Numbers to Correspond to Code) (e.g. XX: AA, AB...YZ, ZZ)</td></tr></tbody></table>			Trace Code	XX - Trace Code (ATMEL Lot Numbers to Correspond to Code) (e.g. XX: AA, AB...YZ, ZZ)	<table border="1"><thead><tr><th>Grade/Lead Finish Material</th></tr></thead><tbody><tr><td>P: Automotive/NIPdAu</td></tr></tbody></table>			Grade/Lead Finish Material	P: Automotive/NIPdAu																
Trace Code																									
XX - Trace Code (ATMEL Lot Numbers to Correspond to Code) (e.g. XX: AA, AB...YZ, ZZ)																									
Grade/Lead Finish Material																									
P: Automotive/NIPdAu																									
<table border="1"><thead><tr><th>Lot Number</th></tr></thead><tbody><tr><td>AAAAAAA - ATMEL Wafer Lot Number</td></tr></tbody></table>			Lot Number	AAAAAAA - ATMEL Wafer Lot Number	<table border="1"><thead><tr><th>ATMEL Truncation</th></tr></thead><tbody><tr><td>AT: ATMEL ATM: ATMEL ATML: ATMEL</td></tr></tbody></table>			ATMEL Truncation	AT: ATMEL ATM: ATMEL ATML: ATMEL																
Lot Number																									
AAAAAAA - ATMEL Wafer Lot Number																									
ATMEL Truncation																									
AT: ATMEL ATM: ATMEL ATML: ATMEL																									
<table border="1"><thead><tr><th>Country of Assembly</th></tr></thead><tbody><tr><td>@ - Country of Assembly</td></tr></tbody></table>			Country of Assembly	@ - Country of Assembly																					
Country of Assembly																									
@ - Country of Assembly																									

Package Mark Contact:
DL-CSO-Assy_eng@atmel.com

TITLE
25080-16-32-64BAM, AT25080B/AT25160B/
AT25320B/AT25640B Automotive Marking Information
for Package Offering

DRAWING NO.
25080-16-32-64BAM

REV.
A

2/2/12