



PCN / EOL Notification

PCN Number: CC132504

Notification Date: July 10, 2013

Title: 64-Kbit 2-wire interface Automotive Grade (-40C to +125C) Serial EEPROM (AT24C64A) Process Geometric Shrink and Device Enhancements

Product Identification:

All Packages of the Automotive Temperature Grade (-40C to +125C) AT24C64A

Reason for Change:

- ☒ Material / Composition
☒ Processing / Manufacturing

- ☒ Design / Firmware
☐ Logistics

- ☐ Manufacturing Location
☐ Quality / Reliability

Change Description:

Atmel has performed a process geometry shrink of the Serial EEPROM Automotive Temperature Grade AT24C64A device (2-wire interface, 64-Kbit density) from 0.35µm to 0.25µm. The catalog part number AT24C64A will be replaced by AT24C64D (see Table 1). The new devices are pin-to-pin and functionally backward compatible with the current AT24C64A devices with the following exceptions and enhancements.

Extended-VCC Operation

With a growing number of application segments moving to lower supply voltages, Atmel is developing next generation devices to meet the needs of these lower voltages. These voltage ranges are used by various MCUs, SoCs, and ASICs as process lithographies for such products continue to reduce. To address these voltage requirements, Atmel has designed the AT24C64D device to operate over a 2.5V to 5.5V range versus the previous 2.7V to 5.5V range

Conversion to Nickel-Palladium-Gold (NiPdAu) lead finish

New devices will be available in the more robust NiPdAu lead finish. The NiPdAu lead finish complies with “green” packaging standards, and all package options remain RoHS compliant and Pb/Halide/Halogen-free. The “P” designation as part of the package designator suffix in the catalog part number identifies the NiPdAu lead finish for Automotive Temperature grade product.

Package material set changes

Atmel assembly subcontractor, Amkor Technology Philippines, SOIC and TSSOP package material sets will change as noted in the following table:

ATP	SOIC		TSSOP	
Material Set	From	To	From	To
Die Attach	Ablebond 84-1 LMISR4	Ablebond 8290	Ablebond 8290	No Change
Wire Diameter	0.8 mil Au	0.6 mil Au	0.8 mil Au	No Change
Mold Compound	Sumitomo EME-G700	Nitto-GE900S	Sumitomo EME-G700	Hitachi CEL-8240HF 10P
Lead Finish	Matte Sn	NiPdAu	Matte Sn	NiPdAu

ATMEL Colorado Springs • 1150 E, Cheyenne Mtn, Blvd Colorado Springs • CO 80906 USA

Delivery Options

To further stream line the shipping and handling process, Atmel is eliminating bulk delivery options. The new AT24C64**D** devices will be offered in Tape and Reel only.

Identification Method to Distinguish Change:

The NEW catalog part numbers use "**D**" suffix for the device revision (AT24C64A changes to AT24C64**D**). Please refer to Attachment A for part marking scheme.

Table 1.

This is the listing for standard datasheet offering, PCN also applies to all (customer specific) special CAN part numbers that are not listed in the table below:

EOL Part Number	Replacement Part Number	Package	Carrier Type
AT24C64AN-10SQ-2.7 ¹	AT24C64D-SSPD-T ³	SOIC	T/R, 4K per reel
AT24C64AN-10SQ-2.7 SL383 ²	AT24C64D-SSPD-T ³	SOIC	T/R, 4K per reel
AT24C64A-10TQ-2.7 ¹	AT24C64D-XPD-T ³	TSSOP	T/R, 5K per reel
AT24C64A-10TQ-2.7 SL383 ²	AT24C64D-XPD-T ³	TSSOP	T/R, 5K per reel

Notes:

- 1. Bulk will no longer be an ordering option, Tape and Reel ordering only offered**
- 2. SL383 will be eliminated and replaced with "-T" to denote Tape and Reel**
- 3. Please reference qualification pack for further details**

Qualification Data:	☒ Available	☐ Will be available (mm/dd/yr):	☐ Not Applicable
Samples:	☒ Available	☐ Will be available (mm/dd/yr):	☐ Not Applicable

Quantifiable Impact on Quality & Reliability:

None

Forecasted Availability Date: Now

Last Time Buy Date: January 9, 2014

Last Ship Date: July 9, 2014

**All orders placed after the notification date are non-cancellable and non-returnable (NCNR).*

Atmel Contact: Please contact your Atmel Sales Representative or Distributor for additional information (when replying via e-mail please include PCN number in subject line).

Information provided herein is in connection with Atmel products and this information is provided "AS IS". Atmel assumes no responsibility for any errors that may appear in this document. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

Attention Distributors: Product(s) identified in this notification will become obsolete and as such this EOL notification will act as the official written notification. All obsolete products will be listed in the next published quarterly distributor price book, following an PCN/EOL change, and listed on the obsolescence form which accompanies said price book. Within thirty (30) days from the published date of the price book, Distributor shall notify Atmel in writing of Distributor's then current inventory of the obsolete product


ATMEL Colorado Springs • 1150 E, Cheyenne Mtn, Blvd Colorado Springs • CO 80906 USA

CUSTOMER ACKNOWLEDGEMENT OF RECEIPT: Atmel requests you acknowledge receipt of this PCN / EOL. Please complete and email to pcnadm@atmel.com and the Atmel Contact listed above. In your acknowledgement, you can grant approval or request additional information.
Atmel will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice.

Company:
Name:
Title:
Date:
Email
Address:
Location:
Comments:

Attachment A

AT24C32D and AT24C64D: Package Marking Information



Note 1: @ designates pin 1

Note 2: Package drawings are not to scale

Catalog Number Truncation			
AT24C32D		Truncation Code ###: 32D	
AT24C64D		Truncation Code ###: 64D	
Date Codes			Voltages
Y = Year	M = Month	WW = Work Week of Assembly	D: 2.5V min
2: 2012	6: 2016	A: January	
3: 2013	7: 2017	B: February	
4: 2014	8: 2018		
5: 2015	9: 2019	L: December	
Country of Assembly		Lot Number	Grade/Lead Finish Material
@ = Country of Assembly		AAA..A = Atmel Wafer Lot Number	P: Automotive/NiPdAu
Trace Code			Atmel Truncation
XX = Trace Code (Atmel Lot Numbers Correspond to Code) Example: AA, AB.... YZ, ZZ			AT: Atmel ATM: Atmel ATML: Atmel

3/13/12

Atmel Package Mark Contact: DL-CSO-Assy_eng@atmel.com	TITLE	DRAWING NO.	REV.
	24C32-64DAM, AT24C32D and AT24C64D Automotive Package Marking Information	24C32-64DAM	B