



Product Change Notification / SYST-01SDNA851

Date:

03-Mar-2021

Product Category:

Clock and Timing - Oscillators

PCN Type:

Document Change

Notification Subject:

Data Sheet - DSA12x2/3/4 - High Performance Differential MEMS Oscillators for Automotive Document Revision

Affected CPNs:

[SYST-01SDNA851_Affected_CPN_03032021.pdf](#)

[SYST-01SDNA851_Affected_CPN_03032021.csv](#)

Notification Text:

SYST-01SDNA851

Microchip has released a new Product Documents for the DSA12x2/3/4 - High Performance Differential MEMS Oscillators for Automotive of devices. If you are using one of these devices please read the document located at [DSA12x2/3/4 - High Performance Differential MEMS Oscillators for Automotive](#).

Notification Status: Final

Description of Change:

- 1) Updated Phase Jitter maximum values for JRMS-CC in the Electrical Characteristics table and added a sixth note.
- 2) Updated package drawing for 6-Lead VDFN 2.5 mm x 2.0 mm Package Outline and Recommended Land Pattern.
- 3) Updated Figure 3-1.

Impacts to Data Sheet: None

Reason for Change: To Improve Manufacturability

Change Implementation Status: Complete

Date Document Changes Effective: 03 Mar 2021

NOTE: Please be advised that this is a change to the document only the product has not been changed.

Markings to Distinguish Revised from Unrevised Devices: N/A

Attachments:

[DSA12x2/3/4 - High Performance Differential MEMS Oscillators for Automotive](#)

Please contact your local [Microchip sales office](#) with questions or concerns regarding this notification.

Terms and Conditions:

If you wish to receive Microchip PCNs via email please register for our PCN email service at our [PCN home page](#) select register then fill in the required fields. You will find instructions about registering for Microchips PCN email service in the [PCN FAQ](#) section.

If you wish to change your PCN profile, including opt out, please go to the [PCN home page](#) select login and sign into your myMicrochip account. Select a profile option from the left navigation bar and make the applicable selections.