



Product Change Notification

Product Change Notification Number: WC124806

Notification Date: February 11, 2013

Title: Die Revision Change for ATxmega64A3U									
Product Identification:									
ATxmega64A3U-AU		ATxmega64A3U-AUR							
ATxmega64A3U-MH		ATxmega64A3U-MHR							
Reason for Change:	☒ Material / Composition ☐ Processing / Manufacturing	☒ Design / Firmware ☐ Logistics	☐ Manufacturing Location ☒ Quality / Reliability						
Change Description: This notification is to advise our customers that Atmel will introduce new revisions of the AVR microcontroller products listed above. The new revisions are package and pin compatible to the existing revisions. They are introduced in order to enhance the product. Actual devices changes are minimal, but for your reference they are listed here together with enhancements that are a pure superset of existing functions. Samples are only available in bulk and can be ordered through Atmel Sample Centre by logging on to https://samples.atmel.com/scripts/samplecenter.dll?atmel?cmd=menu Specific ordering codes for new die revision samples only are shown in the table below, and are available for sample orders only until the proposed first shipment date. For all production orders, only standard existing ordering codes will be accepted. <table border="1"><thead><tr><th>Part number</th><th>Ordering code for samples</th></tr></thead><tbody><tr><td>ATxmega64A3U-AU</td><td>ATxmega64A3U-AUK</td></tr><tr><td>ATxmega64A3U-MH</td><td>ATxmega64A3U-MHK</td></tr></tbody></table> Note that the K in sample ordering codes will not be marked on the package. Changes The new revision change the following: • Reduced current consumption • Chip erase time during programming reduced • Bonding wire material has changed from gold to copper • The I/O pins comply with the JEDEC LVTTTL and LVCMOS specification and the high- and low level input and output voltage limits reflect or exceed this specification. See Appendix 1 for more details on changes.				Part number	Ordering code for samples	ATxmega64A3U-AU	ATxmega64A3U-AUK	ATxmega64A3U-MH	ATxmega64A3U-MHK
Part number	Ordering code for samples								
ATxmega64A3U-AU	ATxmega64A3U-AUK								
ATxmega64A3U-MH	ATxmega64A3U-MHK								
Identification Method to Distinguish Change: For packages where space allows for die ID to be part of marking, new revision material is identified as 35973I.									
Qualification Data:	☒ Available	☐ Will be available (mm/dd/yr):	☐ Not Applicable						
Samples:	☒ Available	☐ Will be available (mm/dd/yr):	☐ Not Applicable						

Quantifiable Impact on Quality & Reliability:

None

Proposed First Ship Date*: May 8, 2013

**The Proposed First Ship Date is the forecasted date that a customer may expect to receive changed product. This is determined by the estimated date of inventory depletion on the PCN issue date. This may be affected by fluctuations in supply and demand. Consequently, although customers should be prepared to receive changed product on this date, Atmel will continue to ship pre-changed product until a time in which inventory has been depleted. This may result in pre-changed product being shipped to customers after this forecasted date.*

Atmel Contact: Please contact your Atmel Sales Representative or Distributor for additional information (when replying via e-mail please include PCN number in subject line).

Information provided herein is in connection with Atmel products and this information is provided "AS IS". Atmel assumes no responsibility for any errors that may appear in this document. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Atmel's Terms and Conditions of Sale for such products, Atmel assumes no liability whatsoever, and Atmel disclaims any express or implied warranty, including liability or warranties relating to fitness for a particular purpose, merchantability, or non-infringement of any patent, copyright or other intellectual property right. Atmel products are not intended for use in a product or system intended to support or sustain life which, if it fails, can be reasonably expected to result in significant personal injury. Atmel may make changes to specifications and product descriptions at any time, without notice.

CUSTOMER ACKNOWLEDGEMENT OF RECEIPT: Atmel requests you acknowledge receipt of this PCN. Please complete and email to pcnadm@atmel.com and the Atmel Contact listed above. In your acknowledgement, you can grant approval or request additional information. **Atmel will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice.**

Company:

Name:

Title:

Date:

Email Address:

Location:

Comments:

Appendix 1: Change Description Details

Reduced current consumption

The table below lists the typical and maximum current consumption in the existing and new revision.

Parameter	Condition		Existing revisions			New revision			Units
			Min	Typ	Max	Min	Typ	Max	
Active power consumption	32kHz, Ext. Clk	V _{CC} = 1.8V		120			50		μA
		V _{CC} = 3.0V		270			125		
	1MHz, Ext. Clk	V _{CC} = 1.8V		350			250		
		V _{CC} = 3.0V		697			520		
	2MHz, Ext. Clk	V _{CC} = 1.8V		658	700		450	550	
		V _{CC} = 3.0V		1.1	1.4		0.9	1.4	mA
	32MHz, Ext. Clk			10.6	15		9.5	15	
Idle power consumption	32kHz, Ext. Clk	V _{CC} = 1.8V		4.3			3.0		μA
		V _{CC} = 3.0V		4.8			4.8		
	1MHz, Ext. Clk	V _{CC} = 1.8V		78			75		
		V _{CC} = 3.0V		150			140		
	2MHz, Ext. Clk	V _{CC} = 1.8V		150	350		145	250	
				290	600		275	450	mA
	32MHz, Ext. Clk			4.7	7.0		4.4	7.0	
Power-down power consumption	T = 25°C	V _{CC} = 3.0V		0.1	1.0		0.1	1.0	
	T = 85°C			1.8	5.0		1.6	5.0	
	WDT and sampled BOD enabled, T = 25°C			1.3	3.0		1.3	3.0	
	WDT and sampled BOD enabled, T = 85°C			3.1	7.0		2.7	7.0	
Power-save power consumption	RTC from ULP clock, WDT and sampled BOD enabled, T = 25°C	V _{CC} = 1.8V		1.2			1.2		
		V _{CC} = 3.0V		1.3			1.3		
	RTC from 1.024kHz low power 32.768kHz TOSC, T = 25°C	V _{CC} = 1.8V		0.6	2.0		0.6	2.0	
		V _{CC} = 3.0V		0.7	2.0		0.7	2.0	
	RTC from low power 32.768kHz TOSC, T = 25°C	V _{CC} = 1.8V		0.8	3.0		0.8	3.0	
		V _{CC} = 3.0V		1.0	3.0		1.0	3.0	
Reset power consumption	Current through RESET pin subtracted	V _{CC} = 3.0V		250			150		

Chip erase time during programming

For the existing revisions the chip erase time is about 105ms, while in the new revision this is lowered to 55ms.